

# GLASSES DUOLUX P

Ref. 60801

TECHNICAL SHEET



*Lux Optical*®

## COLOURS AND MEASUREMENTS

Frame colour	Noir
Frame marking	F
Lens options	Tinted 5
Lens marking	5SO1
Lens standard	En 169

## GENERAL DESCRIPTION AND MATERIALS

- **ABS** frame
- **Lateral** ventilation
- **Adjustable tightening** elastic
- **50 mm diameter** lens
- Protane 5

## SPECIFICAL ADVANTAGES

- **Adjustable tightening** elastic
- **Lateral** ventilation
- Frame resistant to **low energy impacts**
- Lens tinted 5
- Optical **class : 1**
- **Removable lens**

## MAIN APPLICATION FIELDS

- **Mechanical** protection (industry, building)
- **Welding** protection
- **Dust** protection

## PACKAGING

- **Individual** bag
- **200 pairs** in a box
- **25 pairs** in an inner box

## STANDARDIZATION

This glasses is in conformity with the model of individual safety equipment which correspond to

**The CE Type-examination certificate N°I/IST.MASINI/159/95 REV.1**

Delivered by **ISTITUTO DI RICERCHE E COLLAUDI (notified body n° 0068)**

**EN 166**



**EN 169 for lens**

**SACLA** – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tél. : (33) 04 72 26 57 57 – Fax. : (33) 04 72 26 51 70 – Mail : contact@sacla-tm.fr